S.N.	Purchaser's Specifications		Bidder's Compliance Sheet		
	Bed, Hospital	Yes/ No	Ref Docs Page No.	Remarks	
	Manufacturer				
	Brand				
	Type/Model				
	Country of origin				
1	Description of Function	1		1000	
1.1	A hospital bed is a bed specially designed for hospitalized patients				
	in need of patient ease. These beds have special features both for the				
	comfort and well-being of the patient .				
2	Operational Requirements		and the second		
2.1	The patient bed shall be made of solid steel construction with anti-	13.60% I	nd in success	- the trans-	
	corrosive and antirust treated baked hard epoxy powder coating.		and the second		
3	System Configuration				
3.1	Hospital Bed epoxy powder coated.			-	
4	Technical Specifications				
4.1	Bed base shall be anti-corrosive and antirust treated epoxy powder				
	coated welded steel bar or epoxy powder coated 16 gauge perforated				
	sheet top to improve ventilation.				
4.2	The patient bed shall be fixed height with 2 sections where the				
	backrest section could be elevated by mechanical hand crank located				
	at the foot-end of the bed.				
4.3	Shall have 4 IV rod receptacles and mosquito net pole receptacles at				
	the 4 corners.				
4.4	It shall come with one dual hook anti-corrosive and antirust treated				
	epoxy powder coated or 304 grade stainless steel IV rod.				
4.5	Shall have bottom support of size 40x40x2.5mm square MS				
	minimum 3 numbers per bed.				
4.6	Shall have provisions to fix urinary bag on both sides.				
4.7	All 4 legs of the hospital bed shall be capped with heavy duty rubber				
	footings.				
4.8	Bedhead and foot-end panel (head and foot bows) shall be made of				
	either between 4-6 anti-corrosive and antirust treated epoxy powder				
	coated vertical tubular tube of not less than 30mm in diameter.				
4.9	Both bedhead and foot-end panel shall be detachable.				
4.10	The height of the bedhead panel: not less than 1060mm from floor.				
4.11	The height of the foot-end panel: not less than 820mm from floor.				
4.12	Overall approximate dimension: not less than 1980mm length,				
	910mm width, 600mm height				
4.13	The colour of the paint or coating shall be finalised during contract				
	negotiation.				
5	System Configuration Accessories, spares and consumables				
5.1	All standard accessories/consumables/parts required for the proper				
	operation of the above item shall be included in the offer. Bidders				
	shall specify, in a separate Excel worksheet, the quantity and details				
	of any items included in this offer which have not been specified in				
	this Technical Specifications Form.	C. Martin			
6	Operating Environment	The second			
6.1	The system offered shall be designed to store and to operate				
	normally under the conditions of the purchaser's country. The				
	conditions include Climate, Temperature, Humidity, etc.				

Technical Specification of Bed, Hospital

wert Er. Umesh Kumar Chaudhary

भाग प्रदेश न भ मन्त्रविधे गेरा जेक विकास मन्त्र हेवार्ग्या निर्दे

इंस्टिकल सुपरिटल्डल्ट.

7	Purchaser's Specifications	Bidder's Compliance Sheet
7 1	Standards and Safety Requirements	
7.1	Must submit ISO13485 or better or CE certified for medical devices.	
8	Warranty Warranty	
8.1	Warranty for 2 year.	
)	Maintenance Service During Warranty Period	
.1	Standard warranty conditions are applicable. Breakdown	
	maintenance shall be done by supplier during warranty period.	and the second sec
0	Installation and Commissioning	
0.1	Must supply preassembled unit, ready to use.	
1	Documentation	
1.1	Users/Instructions manual shall be manifed in the	
idder m	ust completely fill the Technical Specification Form (TSF). Only Yes/no/all complies should c of all the required parameters must be already	and the second

catalogue of all the required parameters must be clearly mentioned and highlighted. Failure in doing so may lead to rejection of bid from technical committee



भिन्न तरकार भिन्न तरकार भिन्न त भ भिन्न किंद्रान भन्म भीम अम्पताल स्पन्दर्ग

संहिकले सुपरिष्टेन्डन्द